

# Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH)

## CONDURSAL Z0095

Version number: GHS 1.0

Date of compilation: 2016-04-19

### SECTION 1: Identification

#### 1.1 Product identifier

Trade name **CONDURSAL Z0095**  
Registration number (REACH) not relevant (mixture)

#### 1.2 Relevant identified uses of the substance or mixture and uses advised against

Relevant identified uses coating for particular industrial and professional uses

#### 1.3 Details of the supplier of the safety data sheet

Manufacturer:  
NÜSSLE GmbH & Co. KG  
Isoliermittel für Härtetechnik  
Iselshausenstr. 55  
D-72202 NAGOLD  
GERMANY  
mail@nuessle-kg.de  
Phone +49 (0)7452 93205- 0  
Fax +49 (0)7452 93205-20

Supplier:  
THE DUFFY COMPANY  
283 E. Hellen Rd. Palatine, Il. 60067-6954  
USA  
Phone: (847) 202-0000  
Fax (847) 202-0004

Competent person responsible for the safety data sheet B. Schinagl  
e-mail (competent person) mail@nuessle-kg.de

#### 1.4 Emergency telephone number

Emergency information service InfoTrac 1-800-535-5053

### SECTION 2: Hazard(s) identification

#### 2.1 Classification of the substance or mixture

Classification according to Regulation (EC) No 1272/2008 (CLP)

Section	Hazard class	Cat-egory	Hazard class and category	Hazard state-ment
2.6	flammable liquid	Cat. 3	(Flam. Liq. 3)	H226
3.2	skin corrosion/irritation	Cat. 2	(Skin Irrit. 2)	H315
3.3	serious eye damage/eye irritation	Cat. 2	(Eye Irrit. 2)	H319
3.7	reproductive toxicity	Cat. 1B	(Repr. 1B)	H360
3.8R	specific target organ toxicity - single exposure (respiratory tract ir-ritation)	Cat. 3	(STOT SE 3)	H335
3.9	specific target organ toxicity - repeated exposure	Cat. 2	(STOT RE 2)	H373

#### Remarks

For full text of H-phrases: see SECTION 16.

# Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH)

## CONDURSAL Z0095

Version number: GHS 1.0

Date of compilation: 2016-04-19

### The most important adverse physicochemical, human health and environmental effects

Delayed or immediate effects can be expected after short or long-term exposure. The product is combustible and can be ignited by potential ignition sources.

## 2.2 Label elements

### Labeling according to Regulation (EC) No 1272/2008 (CLP)

#### Signal word

Danger

#### Pictograms

GHS02, GHS07,  
GHS08



#### Hazard statements

H226	Flammable liquid and vapor.
H315	Causes skin irritation.
H319	Causes serious eye irritation.
H335	May cause respiratory irritation.
H360	May damage fertility or the unborn child.
H373	May cause damage to organs through prolonged or repeated exposure.

#### Precautionary statements

##### Precautionary statements - prevention

P210	Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
P233	Keep container tightly closed.
P243	Take precautionary measures against static discharge.
P261	Avoid breathing mist/vapors/spray.
P280	Wear protective gloves/eye protection.

##### Precautionary statements - response

P302+P352	IF ON SKIN: Wash with plenty of soap and water.
-----------	---

##### Precautionary statements - storage

P403+P233	Store in a well-ventilated place. Keep container tightly closed.
-----------	--

##### Precautionary statements - disposal

P501	Dispose of contents/container in accordance with local/regional/national/international regulations.
------	---

#### Hazardous ingredients for labelling:

diboron trioxide, Xylene, mixed isomers

## 2.3 Other hazards

Special danger of slipping by leaking/spilling product.

# Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH)

## CONDURSAL Z0095

Version number: GHS 1.0

Date of compilation: 2016-04-19

### SECTION 3: Composition/information on ingredients

#### 3.1 Substances

not relevant (mixture)

#### 3.2 Mixtures

##### Description of the mixture

Name of substance	CAS No	EC No	Wt%	Classification acc. to GHS	Pictograms
diboron trioxide	1303-86-2	215-125-8	25 - < 50	Repr. 1B / H360FD	
Xylene, mixed isomers	1330-20-7	215-535-7	25 - < 50	Flam. Liq. 3 / H226 Acute Tox. 4 / H312 Acute Tox. 4 / H332 Skin Irrit. 2 / H315 Eye Irrit. 2 / H319 STOT SE 3 / H335 STOT RE 2 / H373 Asp. Tox. 1 / H304	  

SVHC: 1303-86-2 Bortrioxid

. For full text of abbreviations: see SECTION 16.

### SECTION 4: First-aid measures

#### 4.1 Description of first-aid measures

##### General notes

Do not leave affected person unattended. Remove victim out of the danger area. Keep affected person warm, still and covered. Take off immediately all contaminated clothing. In all cases of doubt, or when symptoms persist, seek medical advice. In case of unconsciousness place person in the recovery position. Never give anything by mouth.

##### Following inhalation

If breathing is irregular or stopped, immediately seek medical assistance and start first aid actions. In case of respiratory tract irritation, consult a physician. Provide fresh air.

##### Following skin contact

Wash with plenty of soap and water.

##### Following eye contact

Remove contact lenses, if present and easy to do. Continue rinsing. Irrigate copiously with clean, fresh water for at least 10 minutes, holding the eyelids apart.

##### Following ingestion

Rinse mouth with water (only if the person is conscious). Do NOT induce vomiting.

#### 4.2 Most important symptoms and effects, both acute and delayed

Symptoms and effects are not known to date.

#### 4.3 Indication of any immediate medical attention and special treatment needed

none

# Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH)

## CONDURSAL Z0095

Version number: GHS 1.0

Date of compilation: 2016-04-19

### SECTION 5: Fire-fighting measures

#### Extinguishing media

water spray, alcohol resistant foam, BC-powder, carbon dioxide (CO<sub>2</sub>)

#### Unsuitable extinguishing media

water jet

#### 5.2 Special hazards arising from the substance or mixture

In case of insufficient ventilation and/or in use, may form flammable/explosive vapor-air mixture. Solvent vapors are heavier than air and may spread along floors. Places which are not ventilated, e.g. unventilated below ground level areas such as trenches, conduits and shafts, are particularly prone to the presence of flammable substances or mixtures.

#### Hazardous combustion products

nitrogen oxides (NO<sub>x</sub>), carbon monoxide (CO), carbon dioxide (CO<sub>2</sub>)

#### 5.3 Advice for firefighters

In case of fire and/or explosion do not breathe fumes. Co-ordinate firefighting measures to the fire surroundings. Do not allow firefighting water to enter drains or water courses. Collect contaminated firefighting water separately. Fight fire with normal precautions from a reasonable distance.

### SECTION 6: Accidental release measures

#### 6.1 Personal precautions, protective equipment and emergency procedures

##### For non-emergency personnel

Remove persons to safety.

##### For emergency responders

Wear breathing apparatus if exposed to vapors/dust/aerosols/gases.

#### 6.2 Environmental precautions

Keep away from drains, surface and ground water. Retain contaminated washing water and dispose it.

#### 6.3 Methods and material for containment and cleaning up

##### Advices on how to contain a spill

Covering of drains.

##### Advices on how to clean up a spill

Wipe up with absorbent material (e.g. cloth, fleece). Collect spillage (sawdust, kieselgur (diatomite), sand, universal binder).

##### Appropriate containment techniques

Use of adsorbent materials.

##### Other information relating to spills and releases

Place in appropriate containers for disposal. Ventilate affected area.

#### 6.4 Reference to other sections

Hazardous combustion products: see section 5. Personal precautions: see section 8. Disposal considerations: see section 13.

# Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH)

## CONDURSAL Z0095

Version number: GHS 1.0

Date of compilation: 2016-04-19

### SECTION 7: Handling and storage

#### 7.1 Precautions for safe handling

##### Recommendations

##### • Measures to prevent fire as well as aerosol and dust generation

Use local and general ventilation. Avoidance of ignition sources. Keep away from sources of ignition - No smoking. Take precautionary measures against static discharge. Use only in well-ventilated areas. Due to danger of explosion, prevent leakage of vapours into cellars, flues and ditches. Ground/bond container and receiving equipment. Use explosion-proof electrical/ventilating/lighting equipment. Use only non-sparking tools.

##### • Warning

Places which are not ventilated, e.g. unventilated below ground level areas such as trenches, conduits and shafts, are particularly prone to the presence of flammable substances or mixtures. Vapors are heavier than air, spread along floors and form explosive mixtures with air. Vapors may form explosive mixtures with air.

##### Advice on general occupational hygiene

Wash hands after use. Do not to eat, drink and smoke in work areas. Remove contaminated clothing and protective equipment before entering eating areas. Never keep food or drink in the vicinity of chemicals. Never place chemicals in containers that are normally used for food or drink. Keep away from food, drink and animal feedingstuffs.

#### 7.2 Conditions for safe storage, including any incompatibilities

##### Managing of associated risks

##### • Explosive atmospheres

Keep container tightly closed and in a well-ventilated place. Use local and general ventilation. Keep cool. Protect from sunlight.

##### • Flammability hazards

Keep away from sources of ignition - No smoking. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Take precautionary measures against static discharge. Protect from sunlight.

##### Incompatible substances or mixtures

Observe compatible storage of chemicals.

##### Consideration of other advice

##### • Ventilation requirements

Use local and general ventilation. Ground/bond container and receiving equipment.

##### • Packaging compatibilities

Only packagings which are approved (e.g. acc. to ADR) may be used.

#### 7.3 Specific end use(s)

See section 16 for a general overview.

### SECTION 8: Exposure controls/personal protection

#### 8.1 Control parameters

##### National limit values

##### Occupational exposure limit values (Workplace Exposure Limits)

Country	Name of agent	CAS No	Identifier	TWA [ppm]	TWA [mg/m <sup>3</sup> ]	STEL [ppm]	STEL [mg/m <sup>3</sup> ]	Source
US	magnesium oxide	1309-48-4	PEL		15			29 CFR OSHA
US	xylene, mixture of isomers	1330-20-7	PEL	100	435			29 CFR OSHA

##### Notation

STEL Short-term exposure limit: a limit value above which exposure should not occur and which is related to a 15-minute period unless otherwise specified

TWA Time-weighted average (long-term exposure limit): measured or calculated in relation to a reference period of 8 hours time-weighted average

# Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH)

## CONDURSAL Z0095

Version number: GHS 1.0

Date of compilation: 2016-04-19

### Relevant DNELs/DMELs/PNECs and other threshold levels

#### • relevant DNELs of components of the mixture

Name of substance	CAS No	End-point	Threshold level	Protection goal, route of exposure	Used in	Exposure time
Xylene, mixed isomers	1330-20-7	DNEL	289 mg/m <sup>3</sup>	human, inhalatory	worker (industry)	acute - local effects
Xylene, mixed isomers	1330-20-7	DNEL	289 mg/m <sup>3</sup>	human, inhalatory	worker (industry)	acute - systemic effects
Xylene, mixed isomers	1330-20-7	DNEL	180 mg/kg	human, dermal	worker (industry)	chronic - systemic effects
Xylene, mixed isomers	1330-20-7	DNEL	77 mg/m <sup>3</sup>	human, inhalatory	worker (industry)	chronic - systemic effects

#### • relevant PNECs of components of the mixture

Name of substance	CAS No	End-point	Threshold level	Organism	Environmental compartment	Exposure time
diboron trioxide	1303-86-2	PNEC	2.9 mg/l	aquatic organisms	freshwater	short-term (single instance)
diboron trioxide	1303-86-2	PNEC	2.9 mg/l	aquatic organisms	marine water	short-term (single instance)
diboron trioxide	1303-86-2	PNEC	10 mg/l	aquatic organisms	sewage treatment plant (STP)	short-term (single instance)
diboron trioxide	1303-86-2	PNEC	5.7 mg/kg	terrestrial organisms	soil	short-term (single instance)
diboron trioxide	1303-86-2	PNEC	13.7 mg/l	aquatic organisms	water	continuous
Xylene, mixed isomers	1330-20-7	PNEC	0.327 mg/l	aquatic organisms	freshwater	short-term (single instance)
Xylene, mixed isomers	1330-20-7	PNEC	0.327 mg/l	aquatic organisms	marine water	short-term (single instance)
Xylene, mixed isomers	1330-20-7	PNEC	6.58 mg/l	aquatic organisms	sewage treatment plant (STP)	short-term (single instance)
Xylene, mixed isomers	1330-20-7	PNEC	12.46 mg/kg	aquatic organisms	freshwater sediment	short-term (single instance)
Xylene, mixed isomers	1330-20-7	PNEC	12.46 mg/kg	aquatic organisms	marine sediment	short-term (single instance)
Xylene, mixed isomers	1330-20-7	PNEC	2.31 mg/kg	terrestrial organisms	soil	short-term (single instance)
Xylene, mixed isomers	1330-20-7	PNEC	0.327 mg/l	aquatic organisms	water	continuous

## 8.2 Exposure controls

# Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH)

## CONDURSAL Z0095

Version number: GHS 1.0

Date of compilation: 2016-04-19

### Appropriate engineering controls

General ventilation.

### Individual protection measures (personal protective equipment)

#### Eye/face protection

Wear eye/face protection.

#### Skin protection

##### • hand protection

Wear suitable gloves. Chemical protection gloves are suitable, which are tested according to EN 374. Check leak-tightness/impermeability prior to use. In the case of wanting to use the gloves again, clean them before taking off and air them well. For special purposes, it is recommended to check the resistance to chemicals of the protective gloves mentioned above together with the supplier of these gloves.

##### • type of material

FKM: fluoro-elastomer

##### • other protection measures

Take recovery periods for skin regeneration. Preventive skin protection (barrier creams/ointments) is recommended. Wash hands thoroughly after handling.

#### Respiratory protection

In case of inadequate ventilation wear respiratory protection.

#### Environmental exposure controls

Use appropriate container to avoid environmental contamination. Keep away from drains, surface and ground water.

## SECTION 9: Physical and chemical properties

### 9.1 Information on basic physical and chemical properties

#### Appearance

Physical state	liquid (viscous)
Color	dark beige
Odor	characteristic

#### Other physical and chemical parameters

pH (value)	nicht anwendbar not applicable
Melting point/freezing point	not determined
Initial boiling point and boiling range	136 °C
Flash point	24 °C
Evaporation rate	not determined
Flammability (solid, gas)	not relevant (fluid)
Explosive limits	
• lower explosion limit (LEL)	1 vol%
• upper explosion limit (UEL)	7 vol%
Vapor pressure	8 hPa at 20 °C
Density	1.2 - 1.3 g/cm <sup>3</sup>
Solubility(ies)	not determined
Partition coefficient	
n-octanol/water (log KOW)	This information is not available.
Auto-ignition temperature	320 °C
Viscosity	
• dynamic viscosity	10000 - 15000 mPa s at 20 °C
Explosive properties	none
Oxidizing properties	none

# Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH)

## CONDURSAL Z0095

Version number: GHS 1.0

Date of compilation: 2016-04-19

### 9.2 Other information

Solvent content	25 - 35 %
Solid content	65 - 75 %

## SECTION 10: Stability and reactivity

### 10.1 Reactivity

Concerning incompatibility: see below "Conditions to avoid" and "Incompatible materials". The mixture contains reactive substance(s): risk of ignition

• **if heated**

risk of ignition

### 10.2 Chemical stability

See below "Conditions to avoid".

### 10.3 Possibility of hazardous reactions

Reacts with water, releasing excess pressure or heat.

### 10.4 Conditions to avoid

Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

**Hints to prevent fire or explosion**

Use explosion-proof electrical/ventilating/lighting equipment. Use only non-sparking tools. Take precautionary measures against static discharge.

### 10.6 Hazardous decomposition products

Reasonably anticipated hazardous decomposition products produced as a result of use, storage, spill and heating are not known. Hazardous combustion products: see section 5.

## SECTION 11: Toxicological information

### 11.1 Information on toxicological effects

Test data are not available for the complete mixture.

**Classification procedure**

The method for classification of the mixture is based on ingredients of the mixture (additivity formula).

**Classification according to GHS (1272/2008/EC, CLP)**

**Acute toxicity**

Shall not be classified as acutely toxic.

• **Acute toxicity of components of the mixture**

Name of substance	CAS No	Exposure route	ATE
diboron trioxide	1303-86-2	inhalation: dust/mist	>2.12
Xylene, mixed isomers	1330-20-7	dermal	1100
Xylene, mixed isomers	1330-20-7	inhalation: vapor	11

**Skin corrosion/irritation**

Causes skin irritation.

**Serious eye damage/eye irritation**

Causes serious eye irritation.

**Respiratory or skin sensitization**

Shall not be classified as a respiratory or skin sensitizer.



# Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH)

## CONDURSAL Z0095

Version number: GHS 1.0

Date of compilation: 2016-04-19

### Summary of evaluation of the CMR properties

May damage the unborn child.  
May damage fertility.  
Shall not be classified as germ cell mutagenic.  
Shall not be classified as carcinogenic.

### Specific target organ toxicity (STOT)

#### • Specific target organ toxicity - single exposure

May cause respiratory irritation.

#### • Specific target organ toxicity - repeated exposure

May cause damage to organs through prolonged or repeated exposure.

### Aspiration hazard

Shall not be classified as presenting an aspiration hazard.

## SECTION 12: Ecological information

### 12.1 Toxicity

Shall not be classified as hazardous to the aquatic environment.

### 12.2 Persistence and degradability

Data are not available.

### 12.3 Bioaccumulative potential

Data are not available.

### Bioaccumulative potential of components of the mixture

Name of substance	CAS No	BCF	Log KOW	BOD5/COD
Xylene, mixed isomers	1330-20-7		3.15	

### 12.4 Mobility in soil

Data are not available.

### 12.5 Results of PBT and vPvB assessment

Data are not available.

### 12.6 Other adverse effects

Data are not available.

## SECTION 13: Disposal considerations

### 13.1 Waste treatment methods

#### Waste treatment-relevant information

Solvent reclamation/regeneration.

#### Sewage disposal-relevant information

Do not empty into drains. Avoid release to the environment. Refer to special instructions/safety data sheets.

#### Waste treatment of containers/packages

It is a dangerous waste; only packagings which are approved (e.g. acc. to ADR) may be used. Completely emptied packages can be recycled. Handle contaminated packages in the same way as the substance itself.

#### Relevant provisions relating to waste

##### List of wastes

08 01 11x Wastes from MFSU and removal of paint and varnish

# Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH)

## CONDURSAL Z0095

Version number: GHS 1.0

Date of compilation: 2016-04-19

### Remarks


Please consider the relevant national or regional provisions. Waste shall be separated into the categories that can be handled separately by the local or national waste management facilities.

### SECTION 14: Transport information

14.1	UN number	1263
14.2	UN proper shipping name	PAINT
14.3	Transport hazard class(es) Class	3 (flammable liquids)
14.4	Packing group	III (substance presenting low danger)
14.5	Environmental hazards	none (non-environmentally hazardous acc. to the dangerous goods regulations)
14.6	Special precautions for user Provisions for dangerous goods (ADR) should be complied within the premises.	
14.7	Transport in bulk according to Annex II of MARPOL and the IBC Code The cargo is not intended to be carried in bulk.	

### Information for each of the UN Model Regulations


#### • Transport of dangerous goods by road, rail and inland waterway (ADR/RID/ADN)

UN number	1263
Proper shipping name	PAINT
Class	3
Classification code	F1
Packing group	III
Danger label(s)	3
	
Special provisions (SP)	163, 367, 640E, 650
Excepted quantities (EQ)	E1
Limited quantities (LQ)	5 L
Transport category (TC)	3
Tunnel restriction code (TRC)	D/E
Hazard identification No	30

### Remarks

Are not subject to the requirements of ADR if packed in receptacles of not more than 450 litres capacity.

#### • International Maritime Dangerous Goods Code (IMDG)

UN number	1263
Proper shipping name	PAINT
Class	3
Packing group	III
Danger label(s)	3
	
Special provisions (SP)	163, 223, 955
Excepted quantities (EQ)	E1
Limited quantities (LQ)	5 L
EmS	F-E, S-E
Stowage category	E

# Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH)

## CONDURSAL Z0095

Version number: GHS 1.0

Date of compilation: 2016-04-19

### • International Civil Aviation Organization (ICAO-IATA/DGR)

UN number 1263  
Proper shipping name Paint  
Class 3  
Packing group III  
Danger label(s) 3



Special provisions (SP) A3, A72  
Excepted quantities (EQ) E1  
Limited quantities (LQ) 10 L

## SECTION 15: Regulatory information

### 15.1 Safety, health and environmental regulations specific for the product in question

### 15.2 Chemical Safety Assessment

Chemical safety assessments for substances in this mixture were not carried out.

#### National regulations (United States)

##### NFPA

Category	Degree of hazard	Description
Flammability	3	material that can be ignited under almost all ambient temperature conditions
Health	2	material that, under emergency conditions, can cause temporary incapacitation or residual injury
Instability	0	material that is normally stable, even under fire conditions
Special hazard		

Flammability: Flammability hazard

Health: Health hazard

Instability: Instability hazard

##### HMIS

Category	Rating	Description
Chronic	*	chronic (long-term) health effects may result from repeated overexposure
Health	2	temporary or minor injury may occur
Flammability	3	material that can be ignited under almost all ambient temperature conditions
Physical hazard	0	material that is normally stable, even under fire conditions, and will not react with water, polymerize, decompose, condense, or self-react. Non-explosive
Personal protective equipment	-	

Chronic: Chronic hazard

Flammability: Flammability hazard

Health: Health hazard

Personal protective equipment (PPE) for normal use

Personal protective equipment:

Physical hazard: Reactivity

ard:

# Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH)

## CONDURSAL Z0095

Version number: GHS 1.0

Date of compilation: 2016-04-19

### SECTION 16: Other information, including date of preparation or last revision

#### Abbreviations and acronyms

Abbr.	Descriptions of used abbreviations
29 CFR OSHA	29 CFR §1910.1001 - Occupational Safety and Health Standards: Toxic and Hazardous Substances (permissible exposure limits)
Acute Tox.	acute toxicity
ADN	Accord européen relatif au transport international des marchandises dangereuses par voies de navigation intérieures (European Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways)
ADR	Accord européen relatif au transport international des marchandises dangereuses par route (European Agreement concerning the International Carriage of Dangerous Goods by Road)
Asp. Tox.	aspiration hazard
ATE	Acute Toxicity Estimate
BCF	BioConcentration Factor
BOD	Biochemical Oxygen Demand
CAS	Chemical Abstracts Service (service that maintains the most comprehensive list of chemical substances)
CLP	Regulation (EC) No 1272/2008 on classification, labeling and packaging of substances and mixtures
CMR	Carcinogenic, Mutagenic or toxic for Reproduction
COD	chemical oxygen demand
DGR	Dangerous Goods Regulations (see IATA/DGR)
DMEL	Derived Minimal Effect Level
DNEL	Derived No-Effect Level
EC No	The EC Inventory (EINECS, ELINCS and the NLP-list) is the source for the seven-digit EC number, an identifier of substances commercially available within the EU (European Union)
EINECS	European Inventory of Existing Commercial Chemical Substances
ELINCS	European List of Notified Chemical Substances
EmS	Emergency Schedule
Eye Dam.	seriously damaging to the eye
Eye Irrit.	irritant to the eye
Flam. Liq.	flammable liquid
GHS	"Globally Harmonized System of Classification and Labelling of Chemicals" developed by the United Nations
HMIS	Hazardous Materials Identification System
IATA	International Air Transport Association
IATA/DGR	Dangerous Goods Regulations (DGR) for the air transport (IATA)
ICAO	International Civil Aviation Organization
IMDG	International Maritime Dangerous Goods Code
log KOW	n-octanol/water
MARPOL	International Convention for the Prevention of Pollution from Ships (abbr. of "Marine Pollutant")
NFPA	National Fire Protection Association (United States)
NFPA® 704	National Fire Protection Association: Standard System for the Identification of the Hazards of Materials for Emergency Response (United States)
NLP	No-Longer Polymer
PBT	Persistent, Bioaccumulative and Toxic
PEL	permissible exposure limit

# Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH)

## CONDURSAL Z0095

Version number: GHS 1.0

Date of compilation: 2016-04-19

Abbr.	Descriptions of used abbreviations
PNEC	Predicted No-Effect Concentration
ppm	parts per million
REACH	Registration, Evaluation, Authorisation and Restriction of Chemicals
Repr.	reproductive toxicity
RID	Règlement concernant le transport International ferroviaire des marchandises Dangereuses (Regulations concerning the International carriage of Dangerous goods by Rail)
Skin Corr.	corrosive to skin
Skin Irrit.	irritant to skin
STEL	short-term exposure limit
STOT RE	specific target organ toxicity - repeated exposure
STOT SE	specific target organ toxicity - single exposure
TWA	time-weighted average
vPvB	very Persistent and very Bioaccumulative

### Key literature references and sources for data

- Regulation (EC) No. 1907/2006 (REACH), amended by 2015/830/EU
- Regulation (EC) No. 1272/2008 (CLP, EU GHS)

### Classification procedure

Physical and chemical properties: The classification is based on tested mixture.

Health hazards/environmental hazards: The method for classification of the mixture is based on ingredients of the mixture (additivity formula).

### List of relevant phrases (code and full text as stated in chapter 2 and 3)

Code	Text
H226	flammable liquid and vapor
H304	may be fatal if swallowed and enters airways
H312	harmful in contact with skin
H315	causes skin irritation
H319	causes serious eye irritation
H332	harmful if inhaled
H335	may cause respiratory irritation
H360	may damage fertility or the unborn child
H360FD	may damage fertility. May damage the unborn child
H373	may cause damage to organs through prolonged or repeated exposure

### Disclaimer

This information is based upon the present state of our knowledge. This SDS has been compiled and is solely intended for this product.