according to Regulation (EC) No. 1907/2006 (REACH)

## **CONDURSAL N523**

	n number: GHS 3.0 es version of: 2018-10-10	revision: 2021-01-05
SEC	TION 1: Identification	
1.1	Product identifierTrade nameCONDURSALRegistration number (REACH)	- N523 not relevant (mixture)
1.2	Relevant identified uses of the substance or mixing Relevant identified uses	ture and uses advised against coating for particular industrial and professional uses
1.3	Details of the supplier of the safety data sheet NÜSSLE GmbH & Co. KG Iselshauser Str. 55 D-72202 Nagold Germany Telephone: +49 (0) 74 52-9 32 05-0 Telefax: +49 (0) 74 52-9 32 05-20 e-mail: mail@nuessle-kg.de	
1.4	Competent person responsible for the safety data sheet <b>Emergency telephone number</b>	mail@nuessle-kg.de

Emergency information service

This number is only available during the following of-fice hours: +49 (0) 7452-9 32 05-0 Mon-Fri 08:00 AM - 04:00 PM

#### SECTION 2: Hazard(s) identification

#### 2.1 Classification of the substance or mixture Classification according to Regulation (EC) No 1272/2008 (CLP)

Section	Hazard class	Cat- egory	Hazard class and category	Hazard state- ment
A.2	skin corrosion/irritation	Cat. 2	(Skin Irrit. 2)	H315
A.3	serious eye damage/eye irritation	Cat. 2	(Eye Irrit. 2)	H319
A.9	specific target organ toxicity - repeated exposure	Cat. 2	(STOT RE 2)	H373
B.6	flammable liquid	Cat. 3	(Flam. Liq. 3)	H226

#### Remarks

For full text of H-phrases: see SECTION 16.

#### The most important adverse physicochemical, human health and environmental effects

Delayed or immediate effects can be expected after short or long-term exposure. The product is combustible and can be ignited by potential ignition sources.

#### 2.2 Label elements

GHS08

Labeling according to Regulation (EC) No 1272/2008 (CLP) Signal word Warning Pictograms GHS02. GHS07.

Page 1 / 12

according to Regulation (EC) No. 1907/2006 (REACH)

## **CONDURSAL N523**

Version number: GHS 3.0 Replaces version of: 2018-10-10

#### Lionard statements

Hazard statements	
H226 H315 H319 H373	Flammable liquid and vapor. Causes skin irritation. Causes serious eye irritation. May cause damage to organs through prolonged or repeated exposure.
Precautionary state	ments
Precautionary state	ments - prevention
P210 P260 P280	Keep away from heat/sparks/open flames/hot surfaces. No smoking. Do not breathe mist/vapors/spray. Wear protective gloves/eye protection.
Precautionary state	ments - response
P303+P361+P353	If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with wa- ter/shower.
P305+P351+P338	If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P314	Get medical advice/attention if you feel unwell.
P321	Specific treatment (see on this label).
P337+P313	If eye irritation persists: Get medical advice/attention.
P370+P378	In case of fire: Use sand, carbon dioxide or powder extinguisher to extinguish.
Precautionary state	ments - storage

P403+P235	Store in a well-ventilated place. Keep cool.
P404	Store in a closed container.

#### Precautionary statements - disposal

P501 Dispose of contents/container in accordance with local/regional/national/international regulations.

**Xylene** 

#### Hazardous ingredients for labelling:

#### 2.3 Other hazards

Special danger of slipping by leaking/spilling product. **Results of PBT and vPvB assessment** 

This mixture does not contain any substances that are assessed to be a PBT or a vPvB.

#### SECTION 3: Composition/information on ingredients

#### 3.1 **Substances**

not relevant (mixture)

#### 3.2 **Mixtures**

#### Description of the mixture

Name of sub- stance	CAS No	EC No	Wt%	Classification acc. to GHS	Pictograms
Xylene	1330-20-7	215-535-7	10-<25	Acute Tox. 4 / H312 Acute Tox. 4 / H332 Skin Irrit. 2 / H315 Eye Irrit. 2 / H319 STOT SE 3 / H335 STOT RE 2 / H373 Asp. Tox. 1 / H304 Flam. Liq. 3 / H226	

For full text of abbreviations: see SECTION 16.

revision: 2021-01-05

according to Regulation (EC) No. 1907/2006 (REACH)

## **CONDURSAL N523**

Version number: GHS 3.0 Replaces version of: 2018-10-10

#### SECTION 4: First-aid measures

#### 4.1 Description of first- aid measures

#### General notes

Take off immediately all contaminated clothing.

#### **Following inhalation**

In case of respiratory tract irritation, consult a physician. Provide fresh air.

#### Following skin contact

Wash with plenty of soap and water.

#### Following eye contact

Remove contact lenses, if present and easy to do. Continue rinsing. Irrigate copiously with clean, fresh water for at least 10 minutes, holding the eyelids apart.

#### **Following ingestion**

Rinse mouth immediately and drink plenty of water. Do NOT induce vomiting.

#### 4.2 Most important symptoms and effects, both acute and delayed

Symptoms and effects are not known to date.

#### 4.3 Indication of any immediate medical attention and special treatment needed

#### none

#### SECTION 5: Fire-fighting measures

#### 5.1 Extinguishing media

#### Suitable extinguishing media

water spray, alcohol resistant foam, BC-powder, carbon dioxide (CO2)

#### Unsuitable extinguishing media

water jet

#### 5.2 Special hazards arising from the substance or mixture

In case of insufficient ventilation and/or in use, may form flammable/explosive vapor-air mixture. Solvent vapors are heavier than air and may spread along floors. Places which are not ventilated, e.g. unventilated below ground level areas such as trenches, conduits and shafts, are particularly prone to the presence of flammable substances or mixtures.

#### Hazardous combustion products

carbon monoxide (CO), carbon dioxide (CO2)

#### 5.3 Advice for firefighters

In case of fire and/or explosion do not breathe fumes. Coordinate firefighting measures to the fire surroundings. Do not allow firefighting water to enter drains or water courses. Collect contaminated firefighting water separately. Fight fire with normal precautions from a reasonable distance.

#### SECTION 6: Accidental release measures

#### 6.1 Personal precautions, protective equipment and emergency procedures For non-emergency personnel

Provision of sufficient ventilation. Special danger of slipping by leaking/spilling product.

#### 6.2 Environmental precautions

Keep away from drains, surface and ground water. Retain contaminated washing water and dispose of it.

### 6.3 Methods and material for containment and cleaning up Advice on how to contain a spill

Covering of drains.

revision: 2021-01-05

according to Regulation (EC) No. 1907/2006 (REACH)

### **CONDURSAL N523**

Version number: GHS 3.0 Replaces version of: 2018-10-10 revision: 2021-01-05

#### Advice on how to clean up a spill

Wipe up with absorbent material (e.g. cloth, fleece). Collect spillage (sawdust, kieselgur (diatomite), sand, universal binder).

#### Appropriate containment techniques

Use of adsorbent materials.

#### Other information relating to spills and releases

Place in appropriate containers for disposal. Ventilate affected area.

#### 6.4 Reference to other sections

Hazardous combustion products: see section 5. Personal protective equipment: see section 8. Disposal considerations: see section 13.

#### SECTION 7: Handling and storage

#### 7.1 Precautions for safe handling

#### **Recommendations**

#### Measures to prevent fire as well as aerosol and dust generation

Use local and general ventilation. Avoidance of ignition sources. Keep away from sources of ignition - No smoking. Take precautionary measures against static discharge. Use only in well-ventilated areas. Due to danger of explosion, prevent leakage of vapours into cellars, flues and ditches. Ground/bond container and receiving equipment. Use explosion-proof electrical/ventilating/lighting/equipment. Use only non-sparking tools.

#### Warning

Places which are not ventilated, e.g. unventilated below ground level areas such as trenches, conduits and shafts, are particularly prone to the presence of flammable substances or mixtures. Vapors are heavier than air, spread along floors and form explosive mixtures with air. Vapors may form explosive mixtures with air.

#### Advice on general occupational hygiene

Wash hands after use. Do not eat, drink and smoke in work areas. Remove contaminated clothing and protective equipment before entering eating areas. Never keep food or drink in the vicinity of chemicals. Never place chemicals in containers that are normally used for food or drink. Keep away from food, drink and animal feedingstuffs.

#### 7.2 Conditions for safe storage, including any incompatibilities Managing of associated risks

#### 7.2.1.1 • Explosive atmospheres

Keep container tightly closed and in a well-ventilated place. Use local and general ventilation. Keep cool. Protect from sunlight.

#### • Flammability hazards

Keep away from sources of ignition - No smoking. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Take precautionary measures against static discharge. Protect from sunlight.

#### Incompatible substances or mixtures

Observe compatible storage of chemicals.

#### Consideration of other advice

#### Ventilation requirements

Use local and general ventilation. Ground/bond container and receiving equipment.

#### Packaging compatibilities

Only packagings which are approved (e.g. acc. to ADR) may be used.

according to Regulation (EC) No. 1907/2006 (REACH)

## **CONDURSAL N523**

Version number: GHS 3.0 Replaces version of: 2018-10-10 revision: 2021-01-05

#### SECTION 8: Exposure controls/personal protection

#### 8.1 Control parameters

#### National limit values

Occupational exposure limit values (Workplace Exposure Limits)

Cou ntry	Name of agent	CAS No	lden tifier	TWA [ppm]	TWA [mg/ m³]	STEL [ppm]	STEL [mg/ m³]	Ceil- ing-C [ppm]	Ceil- ing-C [mg/ m <sup>3</sup> ]	Nota tion	Sour ce
US	xylene, mixture of isomers	1330-20- 7	PEL	100	435						29 CFR 1910.1 000
US	xylene (dimethyl- benzene)	1330-20- 7	PEL (CA)	100	435	150	655	300			Cal/ OSHA PEL

Notation

Ceiling-C Ceiling value is a limit value above which exposure should not occur STEL Short-term exposure limit: a limit value above which exposure should

Short-term exposure limit: a limit value above which exposure should not occur and which is related to a 15-minute period (unless otherwise specified)

TWA Time-weighted average (long-term exposure limit): measured or calculated in relation to a reference period of 8 hours timeweighted average (unless otherwise specified

### Relevant DNELs/DMELs/PNECs and other threshold levels

#### relevant DNELs of components of the mixture

Name of sub- stance	CAS No	End- point	Threshold level	Protection goal, route of expos- ure	Used in	Exposure time
Xylene	1330-20- 7	DNEL	289 mg/m <sup>3</sup>	human, inhalatory	worker (in- dustry)	acute - local effects
Xylene	1330-20- 7	DNEL	289 mg/m <sup>3</sup>	human, inhalatory	worker (in- dustry)	acute - systemic ef- fects
Xylene	1330-20- 7	DNEL	180 mg/kg	human, dermal	worker (in- dustry)	chronic - systemic ef- fects
Xylene	1330-20- 7	DNEL	77 mg/m <sup>3</sup>	human, inhalatory	worker (in- dustry)	chronic - systemic ef- fects

#### • relevant PNECs of components of the mixture

Name of sub- stance	CAS No	End- point	Threshold level	Organism	Environ- mental com- partment	Exposure time
Xylene	1330-20- 7	PNEC	0.327 <sup>mg</sup> / <sub>l</sub>	aquatic organisms	freshwater	short-term (single in- stance)
Xylene	1330-20- 7	PNEC	0.327 <sup>mg</sup> / <sub>l</sub>	aquatic organisms	marine water	short-term (single in- stance)
Xylene	1330-20- 7	PNEC	12.46 <sup>mg</sup> / <sub>kg</sub>	aquatic organisms	freshwater sedi- ment	short-term (single in- stance)
Xylene	1330-20- 7	PNEC	12.46 <sup>mg</sup> / <sub>kg</sub>	aquatic organisms	marine sedi- ment	short-term (single in- stance)
Xylene	1330-20- 7	PNEC	2.31 <sup>mg</sup> / <sub>kg</sub>	terrestrial organisms	soil	short-term (single in- stance)
Xylene	1330-20- 7	PNEC	0.327 <sup>mg</sup> / <sub>l</sub>	aquatic organisms	water	intermittent release

according to Regulation (EC) No. 1907/2006 (REACH)

## **CONDURSAL N523**

revision: 2021-01-05

version of: 2018-10-10						
Name of sub- stance	CAS No	End- point	Threshold level	Organism	Environ- mental com- partment	Exposure time
Xylene	1330-20- 7	PNEC	6.58 <sup>mg</sup> / <sub>l</sub>	aquatic organisms	sewage treat- ment plant (STP)	short-term (single in- stance)

#### 8.2 Exposure controls

Version number: GHS 3.0

#### Appropriate engineering controls

General ventilation.

#### Individual protection measures (personal protective equipment) Eye/face protection

Use protective eyewear to guard against splash of liquids.

#### Skin protection

#### hand protection

Wear suitable gloves. Chemical protection gloves are suitable, which are tested according to EN 374. Check leak-tightness/impermeability prior to use. In the case of wanting to use the gloves again, clean them before taking off and air them well. For special purposes, it is recommended to check the resistance to chemicals of the protective gloves mentioned above together with the supplier of these gloves.

#### · type of material

CR: chloroprene (chlorobutadiene) rubber, FKM: fluoro-elastomer

#### • other protection measures

Take recovery periods for skin regeneration. Preventive skin protection (barrier creams/ointments) is recommended. Wash hands thoroughly after handling.

#### **Respiratory protection**

During spraying wear suitable respiratory equipment.

#### **Environmental exposure controls**

Use appropriate container to avoid environmental contamination. Keep away from drains, surface and ground water.

#### SECTION 9: Physical and chemical properties

#### 9.1 Information on basic physical and chemical properties

Appearance	
Physical state	liquid (viscous)
Color	green
Odor	characteristic
Other physical and chemical parameters	
pH (value)	not applicable
Melting point/freezing point	not determined
Initial boiling point and boiling range	136 °C
Flash point	24 °C
Evaporation rate	not determined
Flammability (solid, gas)	not relevant (fluid)
Explosive limits	
<ul> <li>lower explosion limit (LEL)</li> </ul>	1 vol%
<ul> <li>upper explosion limit (UEL)</li> </ul>	7 vol%
Vapor pressure	8 hPa at 20 °C
Density	2.9 <sup>g</sup> / <sub>cm³</sub> at 20 °C
Solubility(ies)	not determined

according to Regulation (EC) No. 1907/2006 (REACH)

## **CONDURSAL N523**

revision: 2021-01-05

	Partition coefficient	
	n-octanol/water (log KOW) Auto-ignition temperature Viscosity	This information is not available. 320 °C
	dynamic viscosity	>1,000 mPa s at 20 °C
	Explosive properties	none
	Oxidizing properties	none
9.2	Other information	
	Solvent content	10–15 %
	Solid content	85–90 %

#### SECTION 10: Stability and reactivity

#### 10.1 Reactivity

Version number: GHS 3.0

Replaces version of: 2018-10-10

This material is not reactive under normal ambient conditions. Concerning incompatibility: see below "Conditions to avoid" and "Incompatible materials". The mixture contains reactive substance(s): risk of ignition

## if heated

risk of ignition

#### 10.2 Chemical stability

The material is stable under normal ambient and anticipated storage and handling conditions of temperature and pressure. See below "Conditions to avoid".

#### 10.3 Possibility of hazardous reactions

No known hazardous reactions.

#### 10.4 Conditions to avoid

Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

#### Hints to prevent fire or explosion

-. Use explosion-proof electrical/ventilating/lighting/equipment. Use only non-sparking tools. Take precautionary measures against static discharge.

#### **10.6 Hazardous decomposition products**

Reasonably anticipated hazardous decomposition products produced as a result of use, storage, spill and heating are not known. Hazardous combustion products: see section 5.

#### SECTION 11: Toxicological information

#### 11.1 Information on toxicological effects

Test data are not available for the complete mixture.

#### **Classification procedure**

The method for classification of the mixture is based on ingredients of the mixture (additivity formula).

### Classification according to GHS (1272/2008/EC, CLP)

### Acute toxicity

Shall not be classified as acutely toxic.

#### · Acute toxicity of components of the mixture

Name of substance	CAS No	Exposure route	ATE
Xylene	1330-20-7	dermal	1,100 <sup>mg</sup> / <sub>kg</sub>
Xylene	1330-20-7	inhalation: vapor	11 <sup>mg</sup> / <sub>l</sub> /4h

#### Skin corrosion/irritation

Causes skin irritation.

according to Regulation (EC) No. 1907/2006 (REACH)

## **CONDURSAL N523**

Version number: GHS 3.0 Replaces version of: 2018-10-10 revision: 2021-01-05

#### Serious eye damage/eye irritation

Causes serious eye irritation.

#### Respiratory or skin sensitization

Shall not be classified as a respiratory or skin sensitizer.

#### Summary of evaluation of the CMR properties

Shall not be classified as germ cell mutagenic, carcinogenic nor as a reproductive toxicant.

#### Specific target organ toxicity (STOT)

#### • Specific target organ toxicity - single exposure

Shall not be classified as a specific target organ toxicant (single exposure).

#### • Specific target organ toxicity - repeated exposure

May cause damage to organs through prolonged or repeated exposure.

#### Aspiration hazard

Shall not be classified as presenting an aspiration hazard.

#### SECTION 12: Ecological information

#### 12.1 Toxicity

12.2 Persistence and degradability

Data are not available.

#### 12.3 Bioaccumulative potential

Data are not available.

Bioaccumulative potential of components of the mixture

Name of substance	CAS No	BCF	Log KOW	BOD5/COD
Xylene	1330-20-7		2.77 - 3.15	

#### 12.4 Mobility in soil

Data are not available.

#### **12.5 Results of PBT and vPvB assessment** Data are not available.

#### 12.6 Other adverse effects

Data are not available.

#### SECTION 13: Disposal considerations

#### 13.1 Waste treatment methods

#### Waste treatment-relevant information

Solvent reclamation/regeneration.

#### Sewage disposal-relevant information

Do not empty into drains. Avoid release to the environment. Refer to special instructions/safety data sheets. Waste treatment of containers/packages

#### waste treatment of containers/packages

Completely emptied packages can be recycled. Handle contaminated packages in the same way as the substance itself.

#### Relevant provisions relating to waste

#### List of wastes

08 01 11\* Wastes from MFSU and removal of paint and varnish

#### Remarks

Please consider the relevant national or regional provisions. Waste shall be separated into the categories that can be handled separately by the local or national waste management facilities.

according to Regulation (EC) No. 1907/2006 (REACH)

## **CONDURSAL N523**

Version number: GHS 3.0 revision: 2021-01-05 Replaces version of: 2018-10-10 SECTION 14: Transport information 14.1 UN number 1263 14.2 UN proper shipping name PAINT Transport hazard class(es) 14.3 Class 3 (flammable liquids) 14.4 Packing group III (substance presenting low danger) 14.5 Environmental hazards NONE (non-environmentally hazardous acc. to the dangerous goods regulations) 14.6 Special precautions for user Provisions for dangerous goods (ADR) should be complied within the premises. 14.7 Transport in bulk according to Annex II of MARPOL and the IBC Code The cargo is not intended to be carried in bulk. Information for each of the UN Model Regulations • Transport of dangerous goods by road, rail and inland waterway (ADR/RID/ADN) **UN** number 1263 PAINT Proper shipping name Class 3 Classification code F1 Ш Packing group 3 Danger label(s) Special provisions (SP) 163, 367, 640E, 650 Excepted quantities (EQ) E1 Limited quantities (LQ) 5 L Transport category (TC) 3 Tunnel restriction code (TRC) D/E Hazard identification No 30 Remarks Are not subject to the requirements of ADR if packed in receptacles of not more than 450 litres capacity. • International Maritime Dangerous Goods Code (IMDG) **UN** number 1263 Proper shipping name PAINT Class 3 Packing group Ш Danger label(s) 3 Special provisions (SP) 163, 223, 367, 955 Excepted quantities (EQ) E1 Limited quantities (LQ) 5 L EmS F-E, <u>S-E</u> Stowage category International Civil Aviation Organization (ICAO-IATA/DGR) 1263 **UN** number Proper shipping name Paint Class 3 Packing group Ш Danger label(s) 3 Special provisions (SP) A3, A72, A192 Excepted quantities (EQ) E1 Limited quantities (LQ) 10 L

according to Regulation (EC) No. 1907/2006 (REACH)

### **CONDURSAL N523**

revision: 2021-01-05

#### Version number: GHS 3.0 Replaces version of: 2018-10-10

#### SECTION 15: Regulatory information

## 15.1 Safety, health and environmental regulations specific for the product in question National inventories

Country	Inventory	Status		
US	TSCA	not all ingredients are listed		
Legend				

TSCA Toxic Substance Control Act

#### 15.2 Chemical Safety Assessment

Chemical safety assessments for substances in this mixture were not carried out.

#### SECTION 16: Other information, including date of preparation or last revision

Abbr.	Descriptions of used abbreviations		
29 CFR 1910.1000	29 CFR 1910.1000, Tables Z-1, Z-2, Z-3 - Occupational Safety and Health Standards: Toxic and Hazardous Sub- stances (permissible exposure limits)		
Acute Tox.	Acute toxicity		
ADN	Accord européen relatif au transport international des marchandises dangereuses par voies de navigation intérieures (European Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways)		
ADR	Accord européen relatif au transport international des marchandises dangereuses par route (European Agreement concerning the International Carriage of Dangerous Goods by Road)		
Asp. Tox.	Aspiration hazard		
ATE	Acute Toxicity Estimate		
BCF	Bioconcentration factor		
BOD	Biochemical Oxygen Demand		
Cal/OSHA PEL	California Division of Occupational Safety and Health (Cal/OSHA): Permissible Exposure Limits (PELs)		
CAS	Chemical Abstracts Service (service that maintains the most comprehensive list of chemical substances)		
Ceiling-C	Ceiling value		
CLP	Regulation (EC) No 1272/2008 on classification, labeling and packaging of substances and mixtures		
CMR	Carcinogenic, Mutagenic or toxic for Reproduction		
COD	Chemical oxygen demand		
DGR	Dangerous Goods Regulations (see IATA/DGR)		
DMEL	Derived Minimal Effect Level		
DNEL	Derived No-Effect Level		
EC No	The EC Inventory (EINECS, ELINCS and the NLP-list) is the source for the seven-digit EC number, an identifier of substances commercially available within the EU (European Union)		
EINECS	European Inventory of Existing Commercial Chemical Substances		
ELINCS	European List of Notified Chemical Substances		
EmS	Emergency Schedule		
Eye Dam.	Seriously damaging to the eye		
Eye Irrit.	Irritant to the eye		
Flam. Liq.	Flammable liquid		
GHS	"Globally Harmonized System of Classification and Labelling of Chemicals" developed by the United Nations		

#### Abbreviations and acronyms

according to Regulation (EC) No. 1907/2006 (REACH)

## **CONDURSAL N523**

revision: 2021-01-05

## Version number: GHS 3.0 Replaces version of: 2018-10-10

Abbr.	Descriptions of used abbreviations		
ΙΑΤΑ	International Air Transport Association		
IATA/DGR	Dangerous Goods Regulations (DGR) for the air transport (IATA)		
ICAO	International Civil Aviation Organization		
IMDG	International Maritime Dangerous Goods Code		
log KOW	n-Octanol/water		
MARPOL	International Convention for the Prevention of Pollution from Ships (abbr. of "Marine Pollutant")		
NLP	No-Longer Polymer		
РВТ	Persistent, Bioaccumulative and Toxic		
PEL	Permissible exposure limit		
PNEC	Predicted No-Effect Concentration		
ppm	Parts per million		
REACH	Registration, Evaluation, Authorisation and Restriction of Chemicals		
RID	Règlement concernant le transport International ferroviaire des marchandises Dangereuses (Regulations concern- ing the International carriage of Dangerous goods by Rail)		
Skin Corr.	Corrosive to skin		
Skin Irrit.	Irritant to skin		
STEL	Short-term exposure limit		
STOT RE	Specific target organ toxicity - repeated exposure		
STOT SE	Specific target organ toxicity - single exposure		
TWA Time-weighted average			
vPvB	Very Persistent and very Bioaccumulative		

#### Key literature references and sources for data

- Regulation (EC) No. 1907/2006 (REACH), amended by 2015/830/EU Regulation (EC) No. 1272/2008 (CLP, EU GHS)
- -

#### **Classification procedure**

Physical and chemical properties: The classification is based on tested mixture. Health hazards/environmental hazards: The method for classification of the mixture is based on ingredients of the mixture (additivity formula).

#### List of relevant phrases (code and full text as stated in chapter 2 and 3)

Code	Text
H226	Flammable liquid and vapor.
H304	May be fatal if swallowed and enters airways.
H312	Harmful in contact with skin.
H315	Causes skin irritation.
H319	Causes serious eye irritation.
H332	Harmful if inhaled.
H335	May cause respiratory irritation.
H373	May cause damage to organs through prolonged or repeated exposure.

# Safety Data Sheet according to Regulation (EC) No. 1907/2006 (REACH)

## **CONDURSAL N523**

Version number: GHS 3.0 Replaces version of: 2018-10-10

revision: 2021-01-05

#### Disclaimer

This information is based upon the present state of our knowledge. This SDS has been compiled and is solely intended for this product.