according to Regulation (EC) No. 1907/2006 (REACH)

CONDURSAL N9W

Version number: GHS 3.0 revision: 2021-01-05 Replaces version of: 2018-10-10

SECTION 1: Identification

1.1 Product identifier

Trade name CONDURSAL N9W

Registration number (REACH) not relevant (mixture)

1.2 Relevant identified uses of the substance or mixture and uses advised against

Relevant identified uses coating for particular industrial and professional uses

1.3 Details of the supplier of the safety data sheet

NÜSSLE GmbH & Co. KG Iselshauser Str. 55 D-72202 Nagold Germany

Telephone: +49 (0) 74 52-9 32 05-0 Telefax: +49 (0) 74 52-9 32 05-20 e-mail: mail@nuessle-kg.de

Competent person responsible for the safety data

sheet

a mail@nuessle-kg.de

1.4 Emergency telephone number

Emergency information service

This number is only available during the following office hours: +49 (0) 7452-9 32 05-0 Mon-Fri 08:00 AM - 04:00 PM

SECTION 2: Hazard(s) identification

2.1 Classification of the substance or mixture Classification according to Regulation (EC) No 1272/2008 (CLP)

Section	Hazard class	Cat- egory	Hazard class and category	Hazard state- ment
A.2	skin corrosion/irritation	Cat. 2	(Skin Irrit. 2)	H315
A.3	serious eye damage/eye irritation	Cat. 2	(Eye Irrit. 2)	H319
A.8R	specific target organ toxicity - single exposure (respiratory tract irritation)	Cat. 3	(STOT SE 3)	H335
A.9	specific target organ toxicity - repeated exposure	Cat. 2	(STOT RE 2)	H373
B.6	flammable liquid	Cat. 3	(Flam. Liq. 3)	H226

Remarks

For full text of H-phrases: see SECTION 16.

Supplemental hazard information

Code	Supplemental hazard information
HNOC002	may be harmful in contact with skin (GHS category 5: acutely toxic - dermal)
HNOC003	may be harmful if inhaled (GHS category 5: acutely toxic - inhalation)

The most important adverse physicochemical, human health and environmental effects

Delayed or immediate effects can be expected after short or long-term exposure. The product is combustible and can be ignited by potential ignition sources.

2.2 Label elements

Labeling according to Regulation (EC) No 1272/2008 (CLP)

Signal word Warning

according to Regulation (EC) No. 1907/2006 (REACH)

CONDURSAL N9W

Version number: GHS 3.0 revision: 2021-01-05 Replaces version of: 2018-10-10

Pictograms

GHS02, GHS07, GHS08







Hazard statements

H226 Flammable liquid and vapor.
H315 Causes skin irritation.
H319 Causes serious eye irritation.
H335 May cause respiratory irritation.

H373 May cause damage to organs through prolonged or repeated exposure.

Precautionary statements

Precautionary statements - prevention

P210 Keep away from heat/sparks/open flames/hot surfaces. No smoking.

P241 Use explosion-proof electrical/ventilating/lighting equipment.

P260 Do not breathe mist/vapors/spray. P280 Wear protective gloves/eye protection.

Precautionary statements - response

P303+P361+P353 If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with wa-

ter/shower.

P304+P340 If inhaled: Remove person to fresh air and keep comfortable for breathing.

P305+P351+P338 If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if

present and easy to do. Continue rinsing.

P312 Call a poison center/doctor if you feel unwell. P321 Specific treatment (see ... on this label).

P370+P378 In case of fire: Use sand, carbon dioxide or powder extinguisher to extinguish.

Precautionary statements - storage

P403+P233 Store in a well-ventilated place. Keep container tightly closed.

P403+P235 Store in a well-ventilated place. Keep cool.

Precautionary statements - disposal

P501 Dispose of contents/container in accordance with local/regional/national/international

regulations.

Additional labeling requirements

HNOC002 May be harmful in contact with skin (GHS category 5: acutely toxic - dermal). HNOC003 May be harmful if inhaled (GHS category 5: acutely toxic - inhalation).

Hazardous ingredients for labelling: Xylene

2.3 Other hazards

Special danger of slipping by leaking/spilling product.

Results of PBT and vPvB assessment

This mixture does not contain any substances that are assessed to be a PBT or a vPvB.

SECTION 3: Composition/information on ingredients

3.1 Substances

not relevant (mixture)

3.2 Mixtures

according to Regulation (EC) No. 1907/2006 (REACH)

CONDURSAL N9W

Version number: GHS 3.0 revision: 2021-01-05 Replaces version of: 2018-10-10

Description of the mixture

Name of sub- stance	CAS No	EC No	Wt%	Classification acc. to GHS	Pictograms
Xylene	1330-20-7	215-535-7	25 - < 50	Acute Tox. 4 / H312 Acute Tox. 4 / H332 Skin Irrit. 2 / H315 Eye Irrit. 2 / H319 STOT SE 3 / H335 STOT RE 2 / H373 Asp. Tox. 1 / H304 Flam. Liq. 3 / H226	

For full text of abbreviations: see SECTION 16.

SECTION 4: First-aid measures

4.1 Description of first- aid measures

General notes

Take off immediately all contaminated clothing.

Following inhalation

In case of respiratory tract irritation, consult a physician. Provide fresh air.

Following skin contact

Wash with plenty of soap and water.

Following eye contact

Remove contact lenses, if present and easy to do. Continue rinsing. Irrigate copiously with clean, fresh water for at least 10 minutes, holding the eyelids apart.

Following ingestion

Rinse mouth immediately and drink plenty of water. Do NOT induce vomiting.

4.2 Most important symptoms and effects, both acute and delayed

Symptoms and effects are not known to date.

4.3 Indication of any immediate medical attention and special treatment needed

none

SECTION 5: Fire-fighting measures

5.1 Extinguishing media

Suitable extinguishing media

water spray, alcohol resistant foam, BC-powder, carbon dioxide (CO2)

Unsuitable extinguishing media

water jet

5.2 Special hazards arising from the substance or mixture

In case of insufficient ventilation and/or in use, may form flammable/explosive vapor-air mixture. Solvent vapors are heavier than air and may spread along floors. Places which are not ventilated, e.g. unventilated below ground level areas such as trenches, conduits and shafts, are particularly prone to the presence of flammable substances or mixtures.

Hazardous combustion products

carbon monoxide (CO), carbon dioxide (CO2)

5.3 Advice for firefighters

In case of fire and/or explosion do not breathe fumes. Coordinate firefighting measures to the fire surroundings. Do not allow firefighting water to enter drains or water courses. Collect contaminated firefighting water separately. Fight fire with normal precautions from a reasonable distance.

according to Regulation (EC) No. 1907/2006 (REACH)

CONDURSAL N9W

Version number: GHS 3.0 revision: 2021-01-05 Replaces version of: 2018-10-10

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures

For non-emergency personnel

Provision of sufficient ventilation. Special danger of slipping by leaking/spilling product.

6.2 Environmental precautions

Keep away from drains, surface and ground water. Retain contaminated washing water and dispose of it.

6.3 Methods and material for containment and cleaning up

Advice on how to contain a spill

Covering of drains.

Advice on how to clean up a spill

Wipe up with absorbent material (e.g. cloth, fleece). Collect spillage (sawdust, kieselgur (diatomite), sand, universal binder).

Appropriate containment techniques

Use of adsorbent materials.

Other information relating to spills and releases

Place in appropriate containers for disposal. Ventilate affected area.

6.4 Reference to other sections

Hazardous combustion products: see section 5. Personal protective equipment: see section 8. Disposal considerations: see section 13.

SECTION 7: Handling and storage

7.1 Precautions for safe handling

Recommendations

• Measures to prevent fire as well as aerosol and dust generation

Use local and general ventilation. Avoidance of ignition sources. Keep away from sources of ignition - No smoking. Take precautionary measures against static discharge. Use only in well-ventilated areas. Due to danger of explosion, prevent leakage of vapours into cellars, flues and ditches. Ground/bond container and receiving equipment. Use explosion-proof electrical/ventilating/lighting/equipment. Use only non-sparking tools.

Warning

Places which are not ventilated, e.g. unventilated below ground level areas such as trenches, conduits and shafts, are particularly prone to the presence of flammable substances or mixtures. Vapors are heavier than air, spread along floors and form explosive mixtures with air. Vapors may form explosive mixtures with air.

Advice on general occupational hygiene

Wash hands after use. Do not eat, drink and smoke in work areas. Remove contaminated clothing and protective equipment before entering eating areas. Never keep food or drink in the vicinity of chemicals. Never place chemicals in containers that are normally used for food or drink. Keep away from food, drink and animal feedingstuffs.

7.2 Conditions for safe storage, including any incompatibilities

Managing of associated risks

7.2.1.1 • Explosive atmospheres

Keep container tightly closed and in a well-ventilated place. Use local and general ventilation. Keep cool. Protect from sunlight.

Flammability hazards

Keep away from sources of ignition - No smoking. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Take precautionary measures against static discharge. Protect from sunlight.

Incompatible substances or mixtures

Observe compatible storage of chemicals.

according to Regulation (EC) No. 1907/2006 (REACH)

CONDURSAL N9W

Version number: GHS 3.0 revision: 2021-01-05 Replaces version of: 2018-10-10

Consideration of other advice

Ventilation requirements

Use local and general ventilation. Ground/bond container and receiving equipment.

Packaging compatibilities

Only packagings which are approved (e.g. acc. to ADR) may be used.

SECTION 8: Exposure controls/personal protection

8.1 **Control parameters**

National limit values

Occupational exposure limit values (Workplace Exposure Limits)

Country	Name of agent	CAS No	lden tifier	TWA [ppm]	TWA [mg/ m³]	STEL [ppm]	STEL [mg/ m³]	Ceil- ing-C [ppm]	Ceil- ing-C [mg/ m³]	Nota tion	Sour ce
US	xylene, mixture of isomers	1330-20- 7	PEL	100	435						29 CFR 1910.1 000
US	xylene (dimethyl- benzene)	1330-20- 7	PEL (CA)	100	435	150	655	300			Cal/ OSHA PEL

Notation

Ceiling-C STEL

Ceiling value is a limit value above which exposure should not occur

Short-term exposure limit: a limit value above which exposure should not occur and which is related to a 15-minute period

(unless otherwise specified) TWA

Time-weighted average (long-term exposure limit): measured or calculated in relation to a reference period of 8 hours time-weighted average (unless otherwise specified

Relevant DNELs/DMELs/PNECs and other threshold levels

• relevant DNELs of components of the mixture

Name of sub- stance	CAS No	End- point	Threshold level	Protection goal, route of expos- ure	Used in	Exposure time
Xylene	1330-20- 7	DNEL	289 mg/m ³	human, inhalatory	worker (in- dustry)	acute - local effects
Xylene	1330-20- 7	DNEL	289 mg/m ³	human, inhalatory	worker (in- dustry)	acute - systemic ef- fects
Xylene	1330-20- 7	DNEL	180 mg/kg	human, dermal	worker (in- dustry)	chronic - systemic ef- fects
Xylene	1330-20- 7	DNEL	77 mg/m³	human, inhalatory	worker (in- dustry)	chronic - systemic ef- fects

• relevant PNECs of components of the mixture

Name of sub- stance	CAS No	End- point	Threshold level	Organism	Environ- mental com- partment	Exposure time
Xylene	1330-20- 7	PNEC	0.327 ^{mg} / _l	aquatic organisms	freshwater	short-term (single in- stance)
Xylene	1330-20- 7	PNEC	0.327 ^{mg} / _l	aquatic organisms	marine water	short-term (single in- stance)
Xylene	1330-20- 7	PNEC	12.46 ^{mg} / _{kg}	aquatic organisms	freshwater sedi- ment	short-term (single in- stance)
Xylene	1330-20- 7	PNEC	12.46 ^{mg} / _{kg}	aquatic organisms	marine sedi- ment	short-term (single in- stance)

according to Regulation (EC) No. 1907/2006 (REACH)

CONDURSAL N9W

Version number: GHS 3.0 revision: 2021-01-05 Replaces version of: 2018-10-10

Name of sub- stance	CAS No	End- point	Threshold level	Organism	Environ- mental com- partment	Exposure time
Xylene	1330-20- 7	PNEC	2.31 ^{mg} / _{kg}	terrestrial organisms	soil	short-term (single in- stance)
Xylene	1330-20- 7	PNEC	0.327 ^{mg} / _l	aquatic organisms	water	intermittent release
Xylene	1330-20- 7	PNEC	6.58 ^{mg} / _I	aquatic organisms	sewage treat- ment plant (STP)	short-term (single in- stance)

8.2 Exposure controls

Appropriate engineering controls

General ventilation.

Individual protection measures (personal protective equipment)

Eye/face protection

Use protective eyewear to guard against splash of liquids.

Skin protection

hand protection

Wear suitable gloves. Chemical protection gloves are suitable, which are tested according to EN 374. Check leak-tightness/impermeability prior to use. In the case of wanting to use the gloves again, clean them before taking off and air them well. For special purposes, it is recommended to check the resistance to chemicals of the protective gloves mentioned above together with the supplier of these gloves.

· type of material

CR: chloroprene (chlorobutadiene) rubber, NBR: acrylonitrile-butadiene rubber, IIR: isobutene-isoprene (butyl) rubber, FKM: fluoro-elastomer

other protection measures

Take recovery periods for skin regeneration. Preventive skin protection (barrier creams/ointments) is recommended. Wash hands thoroughly after handling.

Respiratory protection

During spraying wear suitable respiratory equipment.

Environmental exposure controls

Use appropriate container to avoid environmental contamination. Keep away from drains, surface and ground water.

SECTION 9: Physical and chemical properties

9.1 Information on basic physical and chemical properties

Appearance

Physical state liquid (viscous)

Color blue

Odor characteristic

Other physical and chemical parameters

pH (value) not applicable
Melting point/freezing point not determined

Initial boiling point and boiling range 136 °C Flash point 24 °C

Evaporation rate not determined Flammability (solid, gas) not relevant (fluid)

Explosive limits

• lower explosion limit (LEL) 1 vol%

according to Regulation (EC) No. 1907/2006 (REACH)

CONDURSAL N9W

Version number: GHS 3.0 revision: 2021-01-05 Replaces version of: 2018-10-10

 upper explosion limit (UEL) 7 vol%

Vapor pressure 8 hPa at 20 °C

Density 1.1 - 1.2 9/cm3 at 20 °C

Solubility(ies) not determined

Partition coefficient

n-octanol/water (log KOW) This information is not available.

320 °C Auto-ignition temperature

Viscosity

 dynamic viscosity >1.000 mPa s at 20 °C

Explosive properties none Oxidizing properties none

9.2 Other information

> Solvent content 30 - 55 % Solid content 45 - 70 %

SECTION 10: Stability and reactivity

10.1 Reactivity

This material is not reactive under normal ambient conditions. Concerning incompatibility: see below "Conditions to avoid" and "Incompatible materials". The mixture contains reactive substance(s): risk of ignition

if heated

risk of ignition

10.2 Chemical stability

The material is stable under normal ambient and anticipated storage and handling conditions of temperature and pressure. See below "Conditions to avoid".

Possibility of hazardous reactions 10.3

No known hazardous reactions.

10.4 Conditions to avoid

Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

Hints to prevent fire or explosion

-. Use explosion-proof electrical/ventilating/lighting/equipment. Use only non-sparking tools. Take precautionary measures against static discharge.

Hazardous decomposition products 10.6

Reasonably anticipated hazardous decomposition products produced as a result of use, storage, spill and heating are not known. Hazardous combustion products: see section 5.

SECTION 11: Toxicological information

Information on toxicological effects 11.1

Test data are not available for the complete mixture.

Classification procedure

The method for classification of the mixture is based on ingredients of the mixture (additivity formula).

Classification according to GHS (1272/2008/EC, CLP)

Acute toxicity

Shall not be classified as acutely toxic.

GHS of the United Nations, annex 4: May be harmful in contact with skin or if inhaled.

according to Regulation (EC) No. 1907/2006 (REACH)

CONDURSAL N9W

Version number: GHS 3.0 revision: 2021-01-05 Replaces version of: 2018-10-10

Acute toxicity of components of the mixture

Name of substance	CAS No	Exposure route	ATE
Xylene	1330-20-7	dermal	1,100 ^{mg} / _{kg}
Xylene	1330-20-7	inhalation: vapor	11 ^{mg} / _l /4h

Skin corrosion/irritation

Causes skin irritation.

Serious eye damage/eye irritation

Causes serious eye irritation.

Respiratory or skin sensitization

Shall not be classified as a respiratory or skin sensitizer.

Summary of evaluation of the CMR properties

Shall not be classified as germ cell mutagenic, carcinogenic nor as a reproductive toxicant.

Specific target organ toxicity (STOT)

• Specific target organ toxicity - single exposure

May cause respiratory irritation.

• Specific target organ toxicity - repeated exposure

May cause damage to organs through prolonged or repeated exposure.

Aspiration hazard

Shall not be classified as presenting an aspiration hazard.

SECTION 12: Ecological information

12.1 Toxicity

12.2 Persistence and degradability

Data are not available.

12.3 Bioaccumulative potential

Data are not available.

Bioaccumulative potential of components of the mixture

Name of substance	CAS No	BCF	Log KOW	BOD5/COD
Xylene	1330-20-7		2.77 – 3.15	

12.4 Mobility in soil

Data are not available.

12.5 Results of PBT and vPvB assessment

Data are not available.

12.6 Other adverse effects

Data are not available.

according to Regulation (EC) No. 1907/2006 (REACH)

CONDURSAL N9W

Version number: GHS 3.0 revision: 2021-01-05 Replaces version of: 2018-10-10

SECTION 13: Disposal considerations

13.1 Waste treatment methods

Waste treatment-relevant information

Solvent reclamation/regeneration.

Sewage disposal-relevant information

Do not empty into drains. Avoid release to the environment. Refer to special instructions/safety data sheets.

Waste treatment of containers/packages

Completely emptied packages can be recycled. Handle contaminated packages in the same way as the substance itself.

Relevant provisions relating to waste

List of wastes

08 01 11* Wastes from MFSU and removal of paint and varnish

Remarks

Please consider the relevant national or regional provisions. Waste shall be separated into the categories that can be handled separately by the local or national waste management facilities.

SECTION 14: Transport information

14.1	UN number	1263
14.2	UN proper shipping name	PAINT
14.3	Transport hazard class(es) Class	3 (flammable liquids)
14.4	Packing group	III (substance presenting low danger)
14.5	Environmental hazards	none (non-environmentally hazardous acc. to the dangerous goods regulations)
1/16	Special progautions for user	

14.6 Special precautions for user

Provisions for dangerous goods (ADR) should be complied within the premises.

14.7 Transport in bulk according to Annex II of MARPOL and the IBC Code

The cargo is not intended to be carried in bulk.

Information for each of the UN Model Regulations

• Transport of dangerous goods by road, rail and inland waterway (ADR/RID/ADN)

UN number	1263
Proper shipping name	PAINT
Class	3
Classification code	F1
Packing group	III
Danger label(s)	3
Special provisions (SP)	163. 36

Special provisions (SP) 163, 367, 640E, 650

Excepted quantities (EQ)

Limited quantities (LQ)

Transport category (TC)

Tunnel restriction code (TRC)

Hazard identification No

E1

5 L

D/E

Remarks

Are not subject to the requirements of ADR if packed in receptacles of not more than 450 litres capacity.

according to Regulation (EC) No. 1907/2006 (REACH)

CONDURSAL N9W

Version number: GHS 3.0 revision: 2021-01-05 Replaces version of: 2018-10-10

• International Maritime Dangerous Goods Code (IMDG)

UN number 1263
Proper shipping name PAINT
Class 3
Packing group III
Danger label(s) 3

Special provisions (SP) 163, 223, 367, 955

 $\begin{array}{lll} \text{Excepted quantities (EQ)} & & \text{E1} \\ \text{Limited quantities (LQ)} & & 5 \text{ L} \\ \text{EmS} & & \text{F-E, $\underline{\text{S-E}}} \\ \text{Stowage category} & & \text{A} \\ \end{array}$

• International Civil Aviation Organization (ICAO-IATA/DGR)

UN number 1263
Proper shipping name Paint
Class 3
Packing group III
Danger label(s) 3

Special provisions (SP) A3, A72, A192

Excepted quantities (EQ) E1
Limited quantities (LQ) 10 L

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations specific for the product in question

15.2 Chemical Safety Assessment

Chemical safety assessments for substances in this mixture were not carried out.

SECTION 16: Other information, including date of preparation or last revision

Abbreviations and acronyms

Abbr.	Descriptions of used abbreviations
29 CFR 1910.1000	29 CFR 1910.1000, Tables Z-1, Z-2, Z-3 - Occupational Safety and Health Standards: Toxic and Hazardous Substances (permissible exposure limits)
Acute Tox.	Acute toxicity
ADN	Accord européen relatif au transport international des marchandises dangereuses par voies de navigation intérieures (European Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways)
ADR	Accord européen relatif au transport international des marchandises dangereuses par route (European Agreement concerning the International Carriage of Dangerous Goods by Road)
Asp. Tox.	Aspiration hazard
ATE	Acute Toxicity Estimate
BCF	Bioconcentration factor
BOD	Biochemical Oxygen Demand
Cal/OSHA PEL	California Division of Occupational Safety and Health (Cal/OSHA): Permissible Exposure Limits (PELs)
CAS	Chemical Abstracts Service (service that maintains the most comprehensive list of chemical substances)
Ceiling-C	Ceiling value
CLP	Regulation (EC) No 1272/2008 on classification, labeling and packaging of substances and mixtures
CMR	Carcinogenic, Mutagenic or toxic for Reproduction
COD	Chemical oxygen demand
DGR	Dangerous Goods Regulations (see IATA/DGR)

according to Regulation (EC) No. 1907/2006 (REACH)

CONDURSAL N9W

Version number: GHS 3.0 Replaces version of: 2018-10-10 revision: 2021-01-05

Abbr.	Descriptions of used abbreviations
DMEL	Derived Minimal Effect Level
DNEL	Derived No-Effect Level
EC No	The EC Inventory (EINECS, ELINCS and the NLP-list) is the source for the seven-digit EC number, an identifier of substances commercially available within the EU (European Union)
EINECS	European Inventory of Existing Commercial Chemical Substances
ELINCS	European List of Notified Chemical Substances
EmS	Emergency Schedule
Eye Dam.	Seriously damaging to the eye
Eye Irrit.	Irritant to the eye
Flam. Liq.	Flammable liquid
GHS	"Globally Harmonized System of Classification and Labelling of Chemicals" developed by the United Nations
IATA	International Air Transport Association
IATA/DGR	Dangerous Goods Regulations (DGR) for the air transport (IATA)
ICAO	International Civil Aviation Organization
IMDG	International Maritime Dangerous Goods Code
log KOW	n-Octanol/water
MARPOL	International Convention for the Prevention of Pollution from Ships (abbr. of "Marine Pollutant")
NLP	No-Longer Polymer
PBT	Persistent, Bioaccumulative and Toxic
PEL	Permissible exposure limit
PNEC	Predicted No-Effect Concentration
ppm	Parts per million
REACH	Registration, Evaluation, Authorisation and Restriction of Chemicals
RID	Règlement concernant le transport International ferroviaire des marchandises Dangereuses (Regulations concerning the International carriage of Dangerous goods by Rail)
Skin Corr.	Corrosive to skin
Skin Irrit.	Irritant to skin
STEL	Short-term exposure limit
STOT RE	Specific target organ toxicity - repeated exposure
STOT SE	Specific target organ toxicity - single exposure
TWA	Time-weighted average
vPvB	Very Persistent and very Bioaccumulative

Key literature references and sources for data

- Regulation (EC) No. 1907/2006 (REACH), amended by 2015/830/EU Regulation (EC) No. 1272/2008 (CLP, EU GHS)

Classification procedure

Physical and chemical properties: The classification is based on tested mixture.

Health hazards/environmental hazards: The method for classification of the mixture is based on ingredients of the mixture (additivity formula).

Safety Data Sheet according to Regulation (EC) No. 1907/2006 (REACH)

CONDURSAL N9W

Version number: GHS 3.0 Replaces version of: 2018-10-10 revision: 2021-01-05

List of relevant phrases (code and full text as stated in chapter 2 and 3)

Code	Text
H226	Flammable liquid and vapor.
H304	May be fatal if swallowed and enters airways.
H312	Harmful in contact with skin.
H315	Causes skin irritation.
H319	Causes serious eye irritation.
H332	Harmful if inhaled.
H335	May cause respiratory irritation.
H373	May cause damage to organs through prolonged or repeated exposure.

Disclaimer

This information is based upon the present state of our knowledge. This SDS has been compiled and is solely intended for this product.